



Product Service

CERTIFICATE

No. Z2 072092 0288 Rev. 10

Holder of Certificate: Shanghai JA Solar Technology Co., Ltd.

No. 118, Lane 3111,
West Huancheng Road
Fengxian District
201401 Shanghai
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product:

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules
Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 704061209505-38

Valid until: 2024-12-10

Date, 2019-12-11

(Zhulin Zhang)

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證書 ◆ CERTIFICADO ◆ CERTIFICAT



Product Service

CERTIFICATE

No. Z2 072092 0288 Rev. 10

Model(s):

Maximum System Voltage: 1000 V DC or 1500 V DC
 JAM72S01-xxx/PR, JAM72S04-xxx/PR, JAM72S06-xxx/PR,
 xxx=325 to 390 in step of 5;
 JAM60S01-xxx/PR, JAM60S04-xxx/PR, JAM60S06-xxx/PR,
 xxx=280 to 325 in step of 5;
 JAM72S01-xxx/SC, JAM72S04-xxx/SC, xxx =320 to 365 in step of 5;
 JAM60S01-xxx/SC, JAM60S04-xxx/SC, JAM60S06-xxx/SC,
 xxx=265 to 300 in step of 5;
 JAM72S03-xxx/PR, xxx=355 to 400 in step of 5;
 JAM60S03-xxx/PR, xxx = 295 to 335 in step of 5;
 JAM72S01-xxx/MR, xxx= 360 to 390 in step of 5;
 JAM60S01-xxx/MR, xxx= 300 to 330 in step of 5;
 JAM72S09-xxx/PR, xxx= 365 to 405 in step of 5;
 JAM60S09-xxx/PR, xxx= 305 to 335 in step of 5;
 JAM72S10-xxx/PR, xxx= 365 to 415 in step of 5;
 JAM60S10-xxx/PR, xxx= 305 to 345 in step of 5;
 JAM72S10-xxx/MR, xxx= 390 to 410 in step of 5;
 JAM60S10-xxx/MR, xxx= 320 to 340 in step of 5;
 JAM78S10-xxx/MR, xxx= 410 to 450 in step of 5;
 JAM66S10-xxx/MR, xxx= 345 to 380 in step of 5;

Maximum System Voltage: 1500 V DC
 JAM6-72-xxx/SI/1500V, xxx =285 to 325 in step of 5;
 JAM6-60-xxx/SI/1500V, xxx =235 to 280 in step of 5;
 JAM6(R)-72-xxx/1500V, xxx =295 to 340 in step of 5;
 JAM6(R)-60-xxx/1500V, JAM6-60-xxx/4BB/1500V,
 xxx =255 to 280 in step of 5;
 JAM6-72-xxx/4BB/1500V, xxx =310 to 335 in step of 5;
 JAM6(L)-72-xxx/PR/1500V, xxx =325 to 345 in step of 5;
 JAM6(L)-60-xxx/PR/1500V, xxx =270 to 295 in step of 5;
 JAM6(K)-72-xxx/PR/1500V, xxx= 335 to 360 in step of 5;
 JAM6(K)-60-xxx/PR/1500V, xxx= 280 to 300 in step of 5;
 JAM6(K)-72-xxx/4BB/1500V, xxx =320 to 340 in step of 5;
 JAM6(K)-60-xxx/4BB /1500V, xxx =265 to 285 in step of 5;

Maximum System Voltage: 1000 V DC
 JAM5(R)-72-xxx, JAM5(R)(BK)-72- xxx, xxx= 195 to 220 in step of 5;
 JAM5-72-xxx, JAM5(BK)-72-xxx, xxx= 155 to 195 in step of 5;
 JAM5(L)-72-xxx, JAM5(L)(BK)-72-xxx, xxx= 155 to 215 in step of 5;
 JAM5-72-xxx/SI, JAM5(BK)-72-xxx/SI, xxx= 180 to 210 in step of 5;
 JAM5(L)-72-xxx/SI, JAM5(L)(BK)-72-xxx/SI, xxx= 180 to 220 in step of 5;
 JAM5(L)-96-xxx, JAM5(L)(BK)-96-xxx, xxx= 210 to 260 in step of 5;
 JAM5(L)-96-xxx/SI, JAM5(L)(BK)-96-xxx/SI; xxx= 240 to 290 in step of 5;
 JAM6-72-xxx, JAM6(BK)-72-xxx, xxx= 255 to 305 in step of 5;
 JAM6-72-xxx/SI, JAM6(BK)-72-xxx/SI, JAM6(SE)-72-xxx/SI,
 xxx= 285 to 325 in step of 5;
 JAM6-60-xxx, JAM6(BK)-60-xxx, xxx= 200 to 250 in step of 5;
 JAM6-60-xxx/3BB, JAM6(BK)-60-xxx/3BB, xxx= 200 to 275 in step of 5;
 JAM6-60-xxx/SI, JAM6(BK)-60-xxx/SI, JAM6(SE)-60-xxx/SI,
 xxx= 235 to 280 in step of 5;
 JAM6-54-xxx, JAM6(BK)-54-xxx; xxx= 180 to 225 in step of 5;
 JAM6-54-xxx/3BB, JAM6(BK)-54-xxx/3BB; xxx= 180 to 250 in step of 5;
 JAM6-72-xxx/3BB, JAM6(BK)-72-xxx/3BB, xxx= 310 to 330 in step of 5;
 JAM6-54-xxx/SI, JAM6(BK)-54-xxx/SI, xxx= 225 to 240 in step of 5;
 JAM6(R)-54-xxx, JAM6(R)(BK)-54-xxx, xxx=230 to 250 in step of 5;
 JAM6(R)-48-xxx, JAM6(R)(BK)-48-xxx, xxx=205 to 225 in step of 5;
 JAM6-48-xxx/SI, JAM6(BK)-48-xxx/SI, xxx=200 to 220 in step of 5;
 JAM6(R)-72-xxx, JAM6(R)(BK)-72-xxx, xxx=295 to 340 in step of 5;
 JAM6(R)-60-xxx, JAM6(R)(BK)-60-xxx, JAM6(L)-60-xxx,
 JAM6(L)(BK)-60-xxx, JAM6-60-xxx/4BB, xxx=255 to 280 in step of 5;
 JAM6(L)-72-xxx, JAM6(L)(BK)-72-xxx, xxx=295 to 335 in step of 5;
 JAM6(TG)-60-xxx/SI, JAM6(BK)(TG)-60-xxx/SI, JAM6(BK)(SE)-60-xxx/SI,
 xxx=250 to 280 in step of 5;
 JAM6(FA)-60-xxx/SI, xxx=255 to 275 in step of 5;
 JAM6(FA)-48-xxx/SI, xxx=205 to 220 in step of 5;
 JAM6(R)(FA)-48-xxx, JAM6(K)-48-xxx/4BB, JAM6(K)(BK)-48-xxx/4BB,
 xxx= 210 to 225 in step of 5;

ZERTIFIKAT • CERTIFICATE • 認證證書 • CERTIFICADO • CERTIFICAT



Product Service

CERTIFICATE

No. Z2 072092 0288 Rev. 10

Parameters:

Construction:	Framed, with Junction box, Cable and Connectors.
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute; No. 10 West Kaifa Road, Yangzhou, 225009 Jiangsu, P. R. China
Application Class:	Class A
Maximum System Voltage:	1000 V DC or 1500 V DC
Fire Safety Class:	Class C

Tested according to:

EN 61730-1:2007/A11:2014
 EN 61730-2:2007/A1:2012
 IEC 61215:2005
 IEC 61730-1:2004
 IEC 61730-1:2004/AMD1:2011
 IEC 61730-1:2004/AMD2:2013
 IEC 61730-2:2004
 IEC 61730-2:2004/AMD1:2011

Production Facility(ies):

072056, 072092, 079395, 090968, 095903, 097323, 101572,
 001783, 089667, 102627, 102852, 104756, 104757, 078666,
 090075, 076053, 078439, 104704, 105721, 105673

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT