



Manufacturer's Declaration

To Benelux:

Ginlong Solis approves the use of Solis inverters in Belgium, Luxembourg, the Netherlands with the maximum DC input power listed in the following table while all other limitations must be observed (current, voltage, etc.)

If the DC input power does not exceed the values listed below and the inverters are installed in these countries, this will not affect the warranty condition of the inverters.

Note: Maximum DC input power is defined under Standard Test Condition (STC)

Model	Countries	Maximum DC Input Power	DC/AC Ratio
Solis-25K	BE,LU,NL	37.5 kW	150%
Solis-30K	BE,LU,NL	45.0 kW	150%
Solis-33K	BE,LU,NL	48.0 kW	145%
Solis-36K-HV	BE,LU,NL	48.0 kW	133%
Solis-40K-HV	BE,LU,NL	48.0 kW	120%
Solis-40K	BE,LU,NL	52.0 kW	130%
Solis-50K	BE,LU,NL	75.0 kW	150%
Solis-60K-4G	BE,LU,NL	78.0 kW	130%
Solis-50K-HV	BE,LU,NL	60.0 kW	120%
Solis-60K-HV	BE,LU,NL	78.0 kW	130%
Solis-70K-HV-4G	BE,LU,NL	84.0 kW	120%

Date and place
Ningbo
2018-12-11

Manufacture Stamp

Zhang Kun

宁波锦浪新能源科技有限公司
NINGBO GINLONG TECHNOLOGIES CO., LTD.

Ningbo Ginlong Technologies Co., Ltd

No. 57 Jintong Road, Seafront (Binhai)
Industrial Park, Xiangshan, Ningbo, Zhejiang,
315712, P.R. China
Tel: (+86) 574 65803377



Manufacturer's Declaration

To Benelux:

Ginlong Solis approves the use of Solis inverters in Belgium, Luxembourg, the Netherlands with the maximum DC input power listed in the following table while all other limitations must be observed (current, voltage, etc.)

If the DC input power does not exceed the values listed below and the inverters are installed in these countries, this will not affect the warranty condition of the inverters.

Note: Maximum DC input power is defined under Standard Test Condition (STC)

Model	Countries	Maximum DC Input Power(Wp)	DC/AC Ratio
Solis-mini-700-4G	BE,LU,NL	1050	150%
Solis-mini-1000-4G	BE,LU,NL	1500	150%
Solis-mini-1500-4G	BE,LU,NL	2250	150%
Solis-mini-2000-4G	BE,LU,NL	3000	150%
Solis-mini-2500-4G	BE,LU,NL	3750	150%
Solis-mini-3000-4G	BE,LU,NL	4200	140%
Solis-mini-3600-4G	BE,LU,NL	5400	150%
Solis-1P2.5K-4G	BE,LU,NL	3250	130%
Solis-1P3K-4G	BE,LU,NL	4500	150%
Solis-1P3.6K-4G	BE,LU,NL	5400	150%
Solis-1P4K-4G	BE,LU,NL	6000	150%
Solis-1P4.6K-4G	BE,LU,NL	6900	150%
Solis-3P5K-4G	BE,LU,NL	7500	150%
Solis-3P6K-4G	BE,LU,NL	9000	150%
Solis-3P8K-4G	BE,LU,NL	12000	150%
Solis-3P9K-4G	BE,LU,NL	12600	140%
Solis-3P10K-4G	BE,LU,NL	13000	130%
Solis-3P12K-4G	BE,LU,NL	18000	150%
Solis-3P15K-4G	BE,LU,NL	22500	150%
Solis-3P17K-4G	BE,LU,NL	23800	140%
Solis-3P20K-4G	BE,LU,NL	26000	130%

Date and place

Ningbo

2018-12-11

Manufacture Stamp

Zhang Kun

宁波锦浪新能源科技有限公司
NINGBO GINLONG TECHNOLOGIES CO., LTD.

Ningbo Ginlong Technologies Co., Ltd

No. 57 Jintong Road, Seafront (Binhai)
Industrial Park, Xiangshan, Ningbo, Zhejiang,
315712, P.R. China
Tel: (+86) 574 65803377